

一般結構用圓管鋼管(CHS)

澳洲標準AS 1163—Cold-Formed Structural Steel Hollow Sections—Circular Hollow Sections

Outside Diameter 外徑 mm	Wall Thickness 厚度 mm	Unit Mass 單位重量 kg/m	Outside Diameter 外徑 mm	Wall Thickness 厚度 mm	Unit Mass 單位重量 kg/m	
21.3	2.6	1.20	88.9	2.6	5.53	
	3.2	1.43		3.2	6.76	
	3.6	1.57		4.0	8.38	
26.9	2.6	1.56		4.8	9.96	
	3.2	1.87		5.0	10.3	
	4.0	2.26		5.5	11.3	
33.7	3.2	2.41		5.9	12.1	
	4.0	2.93		114.3	3.2	8.77
	4.5	3.24			3.6	9.83
42.4	3.2	3.09	4.5		12.2	
	4.0	3.79	4.8		13.0	
	4.9	4.53	5.4		14.5	
48.3	3.2	3.56	6.0		16.0	
	4.0	4.37	139.7		3.0	10.1
	5.4	5.71			3.5	11.8
60.3	3.6	5.03			5.0	16.6
	4.5	6.19		5.4	17.9	
	5.4	7.31				
76.1	2.3	4.19				
	3.2	5.75				
	3.6	6.44				
	4.5	7.95				
	5.9	10.2				
外徑之容許差 Tolerances of Outside Diameter		±1% , 但不可小於 ±0.5mm ±1% , with a minimum of ±0.5mm				
厚度公差 Thickness Tolerances		±10%				
重量公差 Weight Tolerances		-4%				